

Overview

HP EliteBook 1050 G1



- 1. Speakers
- 2. Power Button

Left

- 3. USB 3.0 Charging Port (left), USB 3.0 (right)
- 4. Standard Security Lock Slot (Lock sold separately)

Overview



Right

1. Ambient Light Sensor
2. IR Sensors
3. Privacy Camera (Optional)
4. IR Camera (Optional)
5. Web Cam (Optional)
6. Web Cam LED
7. Power Connector
8. (2) USB Type-C™ with Thunderbolt™ Ports (Supporting DisplayPort™ 1.2 or 1.4, USB 3.1 Gen2, PCIe Gen 3 devices)
9. HDMI 2.0 (Cable not included)
10. Audio-out/Audio-in Combo jack
11. SD Card Reader
12. Fingerprint Sensor (Optional)
13. Glass Clickpad

Overview

AT A GLANCE

- Windows 10 Pro 64, Home 64 Plus, Pro 64 Plus, or FreeDOS
- Full performance industrial design, Aluminum chassis with HP's pike silver color and premium logo. Backlit keyboard in full aluminum deck, chemically strengthened glass touchpad, and collaboration keys. HP Spill Resistant Keyboard with Durakeys, touchpad buttons with Duracoat finish. Diamond cut edges for touchpad and finger print sensor
- Passed MIL-STD-810G testing¹
- Powerful NVIDIA® discrete graphics: NVIDIA® GeForce® GTX 1050 (optional)
- Intel® Integrated graphics: Intel® HD Graphics 630
- Choice of 8th generation Intel® Core™ i7 hexa-core with vPro™ or Intel® Core™ i5 quad-core with vPro™ technology
- Up to two SODIMMs, for system memory up to 32 GB DDR4-2667 MHz
- Supports multi-display, including up to three (3) displays without a docking solution, with hybrid graphics enabled
- Two (2) Thunderbolt™ 3 ports (supporting DP 1.2 or 1.4, USB 3.1, PCIe Gen 3 devices) on the new USB-CTM connector for high speed data/video/audio transfer support²
- Bang and Olufsen audio optimized for high fidelity audio with immersive surround sound with a discrete amp, deep, rich bass and crystal clear dialog without distortion at high volume
- Long life battery solution with a 4-cell (64 WHr) or 6-cell (96 WHr)
- Widescreen 39.6 cm (15.6")-inch diagonal LED-backlit display: FHD (1920x1080, 400 nit) with ultrawide viewing angle, anti-glare, and ambient light sensor; FHD (1920x1080, 650 nit) with ultrawide viewing angle, anti-glare, HP SureView; UHD (3840x2160, 400 nit) with ultrawide viewing angle, anti-glare, and ambient light sensor
- Optional HD webcam and IR camera
- Wireless connectivity options:
 - Intel® Dual Band Wireless-AC 9560 802.11 AC/a/b/g/n (2x2) WiFi® and Bluetooth® 5.0 combo adaptor (vPro™) or,
 - Intel® Dual Band Wireless-AC 9560 802.11 AC/a/b/g/n (2x2) WiFi® and Bluetooth® 5.0 combo adaptor (non-vPro™)
- Two (2) dedicated M.2 drive slots
- Security features including HP Client Security Manager, HP SureClick, HP WorkWise, HP SureView, and HP SureStart Gen 4
- Low halogen HP BIOS technology, including HP Sure Start to identify and recover from unknown BIOS attacks

1. MIL-STD-810G testing is not intended to demonstrate fitness of U.S. Department of Defense (DoD) contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

2. Thunderbolt™ 3 ports support DisplayPort™ 1.2 for UMA base units and DisplayPort™ 1.4 for discrete base units.

NOTE: See important legal disclosures for all listed specs in their respective features sections.

Features

PRODUCT NAME

HP EliteBook 1050 G1

OPERATING SYSTEM

Preinstalled

Windows 10 Pro 64¹
Windows 10 Pro 64 (National Academic only)^{1,2}
Windows 10 Home 64¹
Windows 10 Home Single Language 64¹
FreeDOS 2.0

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows 10 is automatically updated, which is always enabled. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com/>.

2. Some devices for academic use will automatically be updated to Windows 10 Pro Education with the Windows 10 Anniversary Update. Features vary; see <https://aka.ms/ProEducation> for Windows 10 Pro Education feature information.

PROCESSORS

Intel® Core™ i5-8300H with Intel® UHD Graphics 630 Graphics (2.3 GHz base frequency, up to 4 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{3,4,5}
Intel® Core™ i5-8400H vPro™ processor with Intel® UHD Graphics 630 Graphics (2.5 GHz base frequency, up to 4.2 GHz with Intel® Turbo Boost Technology, 8 MB L3 cache, 4 cores)^{2,3,4}
Intel® Core™ i7-8750H with Intel® UHD Graphics 630 Graphics (2.2 GHz base frequency, up to 4.1 GHz with Intel® Turbo Boost Technology, 9 MB L3 cache, 6 cores)^{2,3,4}
Intel® Core™ i7-8850H vPro™ processor with Intel® UHD Graphics 630 Graphics (2.6 GHz base frequency, up to 4.3 GHz with Intel® Turbo Boost Technology, 9 MB L3 cache, 6 cores)^{2,3,4}

Processor Family

8th Generation Intel® Core™ i7 processor (i7-8850H and i7-8750H models)⁴
8th Generation Intel® Core™ i5 processor (i5-8400H and i5-8300H models)⁴

3. Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.

4. Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

5. In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.

CHIPSET

Chipset is integrated with processor.

Features

GRAPHICS

Integrated

Intel® UHD Graphics 630 ⁶

Discrete

NVIDIA® GeForce® GTX 1050 (4 GB DDR5 dedicated) ⁷

6. HD content required to view HD images.

7. Integrated graphics depends on processor. NVIDIA® Optimus™ technology requires an Intel processor, plus an NVIDIA® GeForce® discrete graphics configuration and is available on Windows 10 Pro OS. With NVIDIA® Optimus™ technology, full enablement of all discrete graphics video and display features may not be supported on all systems (e.g. OpenGL applications will run on the integrated GPU or the APU as the case may be).

DISPLAY

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB with Ambient light sensor (1920 x 1080) ^{6,8,9}

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB for HD camera with Ambient light sensor (1920 x 1080) ^{6,8,9}

39.6 cm (15.6") diagonal FHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB for HD camera and IR camera with Ambient light sensor (1920 x 1080) ^{6,8,9}

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB with Ambient light sensor (3840 x 2160) ^{6,8,9}

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB for HD camera with Ambient light sensor (3840 x 2160) ^{6,8,9}

39.6 cm (15.6") diagonal UHD IPS eDP + PSR anti-glare LED-backlit, 400 cd/m², 100% sRGB for HD camera and IR camera with Ambient light sensor (3840 x 2160) ^{6,8,9}

6. HD content required to view HD images.

8. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

9. Sold separately or as an optional feature.

Features

STORAGE AND DRIVES

Primary M.2 Storage

SATA

512 GB M.2 SATA FIPS 140-2 SSD TLC ¹⁰

256 GB SATA SED (Opal 2) TLC ¹⁰

PCIe

256 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰

512 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰

1 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰

2 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰

256 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰

512 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰

Secondary Storage

SATA

512 GB M.2 SATA FIPS 140-2 SSD TLC ¹⁰

256 GB SATA SED (Opal 2) TLC ¹⁰

PCIe

256 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰

512 GB PCIe® NVMe™ M.2 SSD TLC ¹⁰

1 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰

2 TB PCIe® NVMe™ M.2 SSD TLC ¹⁰

256 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰

512 GB PCIe® NVMe™ M.2 SED SSD TLC Opal 2 ¹⁰

¹⁰. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

Features

MEMORY

Maximum Memory

32 GB DDR4-2666 SDRAM ¹¹

Memory

8 GB DDR4-2666 SDRAM (1 x 8 GB) ¹¹

8 GB DDR4-2666 SDRAM (2 x 4 GB) ¹¹

16 GB DDR4-2666 SDRAM (2 X 8 GB) ¹¹

16 GB DDR4-2666 SDRAM (1 X 16 GB) ¹¹

32 GB DDR4-2666 SDRAM (2 X 16 GB) ¹¹

Memory Slots

2 SODIMM

Both slots are upgradeable

System runs at 2666

Supports Dual Channel Memory

11. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, vPro™ ¹²

Intel® Dual Band Wireless-AC 9560 802.11a/b/g/n/ac (2x2) Wi-Fi® and Bluetooth® 5 Combo, non-vPro™ ¹²

NFC

HP Module with NXP NFC Controller NPC300 I2C NCI

Miracast

Support for Miracast ¹³

12. WLAN is an optional or ad-on feature and requires internet service and sold separately. Availability of public wireless access points limited. The specifications for the 802.11ac WLAN are draft specifications and are not final. If the final specifications differ from the draft specifications, it may affect the ability of the notebook to communicate with other 802.11ac WLAN devices.

13. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

COMPATIBILITY

HP Thunderbolt Dock 230W G2

(2UK38AA)

HP Thunderbolt Dock 230W G2 cable

(3XB95AA)

Features

AUDIO/MULTIMEDIA

Audio

- HP Bang & Olufsen Audio
- HP Noise Cancellation Software
- HP Clear Sound Amp
- Camera Privacy Shutter
- Skype for Business Certification
- Intel SST Audio
- Microphone (Dual Array)
- Microphone (World Facing)

Camera

- 720p HD camera ⁶
- HD IR webcam ^{6,14}

6. HD content required to view HD images.

14. Internet access required.

Features

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

DuraKeys
Optional backlit

Pointing Device

Glass ClickPad with chemically etched surface, gesture support, two-way scroll, two-finger zoom (pinch)

Function Keys

F1 - Display switching
F2 - Sure View (if supported otherwise blank)
F3 - Brightness <down>
F4 - Brightness <up>
F5 - Audio mute (with an LED)
F6 - Volume <down>
F7 - Volume <up>
F8 - Mic mute (with an LED)
F9 - Backlit (if supported otherwise blank)
F10 - NumLock (with an LED)
F11 - Wireless (with an LED)
F12 - Calendar
Share screen (with an LED)
Pick Up/Accept/ Answer/Hold (with an LED)
Hang Up/Decline/ Reject (with an LED)

Features

SOFTWARE AND SECURITY

Preinstalled Software

BIOS

- HP BIOSphere Gen4 ¹⁴
- HP Drive Lock & Automatic Drive Lock
- BIOS Update via Network
- Master Boot Record Security
- Power On Authentication
- Secure Erase ¹⁵
- Absolute Persistence Module ¹⁶
- Pre-boot Authentication
- HP Wireless Wakeup

Software

- HP Native Miracast Support ¹²
- HP Velocity
- HP ePrint Driver + JetAdvantage ¹⁷
- HP Hotkey Support - CMIT
- HP Recovery Manager
- HP Jumpstart
- HP Support Assistant ¹⁸
- HP Noise Cancellation Software
- Buy Office (Sold separately)

Manageability Features

- HP Driver Packs ¹⁹
- HP System Software Manager (SSM)
- HP BIOS Config Utility (BCU)
- HP Client Catalog
- HP Manageability Integration Kit Gen2 [20]
- Ivanti Management Suite ²¹

Client Security Software

- HP Client Security Suite Gen4 ²² including:
 - HP Security Manager ²³ (including Credential Manager, HP Password Manager, HP Spare Key)
 - HP Fingerprint Sensor ²⁶
 - HP Device Access Manager
 - HP Power On Authentication
 - Microsoft Defender ²⁴

Features

Security Management

Secure Erase ¹⁸

TPM 2.0 Embedded Security Chip shipped with Windows 10 (Common Criteria EAL4+ Certified)

SATA 0,1 port disablement (viaBIOS)

RAID configurations ²⁷

Serial, USB enable/disable (viaBIOS)

Power-on password (viaBIOS)

Setup password (viaBIOS)

Support for chassis padlocks and cable lock devices

Integrated hood sensor

HP Sure Click ³⁰

HP Sure Start Gen4 ²⁵

HP Sure Run ²⁸

HP Sure Recover ²⁹

Security

TPM

Model:

Version:

Revision:

FIPS 140-2 Compliant:

IPv6 Certification:

No

MD5 Hash: Please follow the instructions below to access MD5 Hash.

UEFI version:

12. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.

14. HP BIOSphere Gen4 requires Intel® or AMD 8th Gen processors. Features may vary depending on the platform and configurations.

15. Secure Erase for the methods outlined in the National Institute of Standards and Technology Special Publication 800-88 "Clear" sanitation method.

16. Absolute agent is shipped turned off, and will be activated when customers activate a purchased subscription. Subscriptions can be purchased for terms ranging multiple years. Service is limited, check with Absolute for availability outside the U.S. The Absolute Recovery Guarantee is a limited warranty. Certain conditions apply. For full details visit:

<http://www.absolute.com/company/legal/agreements/computrace-agreement>. Data Delete is an optional service provided by Absolute Software. If utilized, the Recovery Guarantee is null and void. In order to use the Data Delete service, customers must first sign a Pre-Authorization Agreement and either obtain a PIN or purchase one or more RSA SecurID tokens from Absolute Software.

17. HP ePrint Driver requires an Internet connection to HP web-enabled printer and HP ePrint account registration (for a list of eligible printers, supported documents and image types and other HP ePrint details, see <http://www.hp.com/go/eprintcenter>). Print times and connection speeds may vary.

Features

18. HP Support Assistant requires Windows and Internet access.
19. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
20. HP Manageability Integration Kit can be downloaded from <http://www8.hp.com/us/en/ads/clientmanagement/overview.html>
21. Ivanti Management Suite subscription required.
22. HP Client Security Suite Gen 4 requires Windows and Intel® or AMD 8th generation processors.
23. HP Password Manager requires Internet Explorer or Chrome or FireFox. Some websites and applications may not be supported. User may need to enable or allow the add-on / extension in the internet browser.
24. Microsoft Defender requires Windows 10. Opt in and internet connection required for updates.
25. HP Sure Start Gen4 is available on HP EliteBook products equipped with Intel® 8th generation processors.
26. HP Fingerprint Sensor sold separately or as an optional feature.
27. RAID configuration is optional and does require a second hard drive.
28. HP Sure Run is available on HP Elite products equipped with 8th generation Intel® or AMD® processors.
29. HP Sure Recover is available on HP Elite PCs with 8th generation Intel® or AMD processors and requires an open, wired network connection. Not available on platforms with multiple internal storage drives, Intel® Optane™. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.
30. HP Sure Click is available on select HP platforms and supports Microsoft® Internet Explorer, Google Chrome, and Chromium™. Supported attachments include Microsoft Office (Word, Excel, PowerPoint) and PDF files in read only mode. Check <http://h20195.www2.hp.com/v2/GetDocument.aspx?docname=4AA7-0922ENW> for all compatible platforms as they become available.

Features

POWER

Power Supply

HP Smart 150 W Slim External AC power adapter

Primary Battery

HP Long Life 6-cell, 95.6 Wh Li-ion polymer ^{31, 32}

HP Long Life 4-cell, 64 Wh Li-ion polymer ^{31, 32}

Power Cord

1.0m 3-wire plug (with ground pin)

Battery Life

Up to 16 hours ³³

31. Recharges the battery up to 50% within 30 minutes when the system is off or in standby mode. Power adapter with a minimum capacity of 65 watts is required. After charging has reached 50% capacity, charging will return to normal. Charging time may vary +/-10% due to System tolerance.

32. Recharges the battery up to 90% within 90 minutes when the system is off or in standby mode when used with the power adapter provided with the notebook. After charging has reached 90% capacity, charging speed will return to normal. Charging time may vary +/-10% due to System tolerance

33. Windows 10 MM14 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See <http://www.bapco.com> for additional details.

WEIGHTS & DIMENSIONS

Weight

Starting at 4.54 lb ³³

Starting at 2.06 kg ³³

Dimensions (w x d x h)

14.17 x 9.65 x 0.74 in

36 x 25.4 x 1.89 cm

33. Weight will vary by configuration.

Features

PORTS/SLOTS

Ports

- 2 USB 3.1 Type-C™ with Thunderbolt™ support
- 1 USB 3.0 (charging)
- 1 USB 3.0
- 1 HDMI 2.0 (with Discrete graphics) ³⁴
- 1 HDMI 1.4 (with Integrated graphics) ³⁴
- 1 Headphone/microphone combo jack
- 1 AC power port
- Standard Security Lock Slot (Lock sold separately)

Expansion Slots

- 1 SD Media Reader Slot
- Supports SD, SDHC, SDXC

34. Cables are not included.

SERVICE AND SUPPORT

HP Services offers 1 year and 90 day limited warranty options depending on country. Batteries have a default one year limited warranty except for Long Life batteries which will have same 1-year or 3-year limited warranty as the platform. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. Service levels and response times for HP Care Packs may vary depending on your geographic location. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc> ³⁵

35. HP Care Packs are sold separately. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit <http://www.hp.com/go/cpc>. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.

Features

ENVIRONMENTAL & INDUSTRY

HP EliteBook 1050 G1 Notebook PC

Eco-Label Certifications & declarations	This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: <ul style="list-style-type: none"> • IT ECO declaration • US ENERGY STAR® • EPEAT® Silver registered in the United States. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit http://www.epeat.net for more information. 		
System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a Typically Configured Notebook.		
Energy Consumption (in accordance with US ENERGY STAR® test method)	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	14.76 W	14.96 W	14.65 W
Normal Operation (Long idle)	6.01 W	6.47 W	6.17 W
Sleep	0.78 W	0.82 W	0.76 W
Off	0.58 W	0.58 W	0.54 W
	NOTE: Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.		
Heat Dissipation*	115VAC, 60Hz	230VAC, 50Hz	100VAC, 60Hz
Normal Operation (Short idle)	50 BTU/hr	50 BTU/hr	50 BTU/hr
Normal Operation (Long idle)	21 BTU/hr	22 BTU/hr	21 BTU/hr
Sleep	3 BTU/hr	3 BTU/hr	3 BTU/hr
Off	2 BTU/hr	2 BTU/hr	2 BTU/hr
	NOTE: Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.		

Features

Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)	Sound Power (L_{WAd} , bels)	Sound Pressure (L_{pAm} , decibels)
Typically Configured – Idle	2.8	16
Fixed Disk – Random writes	3.3	25
Longevity and Upgrading	This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the product may include: Spare parts are available throughout the warranty period and or for up to 5 years after the end of production.	
Batteries	This battery(s) in this product comply with EU Directive 2006/66/EC Batteries used in the product do not contain: Mercury greater the 1ppm by weight Cadmium greater than 20ppm by weight Battery size: CR2032 (coin cell) Battery type: Lithium	
Additional Information	<ul style="list-style-type: none"> • This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC. • This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC. • This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986). • This product is in compliance with the IEEE 1680.1 (EPEAT) standard at the Silver level in the U.S. See http://www.epeat.net for registration status by country. Search keyword generator on HP's 3rd party option store for solar generator accessories at http://www.hp.com/go/options • Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043. • This product contains 0% post-consumer recycled plastic (by wt.) • This product is 95.1% recycle-able when properly disposed of at end of life. 	
Packaging Materials	External:	PAPER/Corrugated 295 g
	Internal:	PLASTIC/Polyethylene Expanded - EPE 50 g
		PLASTIC/Polyethylene low density – LDPE 10 g
Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf): <ul style="list-style-type: none"> • Asbestos • Certain Azo Colorants • Certain Brominated Flame Retardants – may not be used as flame retardants in plastics • Cadmium • Chlorinated Hydrocarbons • Chlorinated Paraffins • Formaldehyde • Halogenated Diphenyl Methanes • Lead carbonates and sulfates • Lead and Lead compounds • Mercuric Oxide Batteries • Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. • Ozone Depleting Substances 	

Features

	<ul style="list-style-type: none"> • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyl Ethers (PBBEs) • Polybrominated Biphenyl Oxides (PBBOs) • Polychlorinated Biphenyl (PCB) • Polychlorinated Terphenyls (PCT) • Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. • Radioactive Substances • Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
<p>Packaging Usage</p>	<p>This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/gse.pdf):</p> <ul style="list-style-type: none"> • Asbestos • Certain Azo Colorants • Certain Brominated Flame Retardants – may not be used as flame retardants in plastics • Cadmium • Chlorinated Hydrocarbons • Chlorinated Paraffins • Formaldehyde • Halogenated Diphenyl Methanes • Lead carbonates and sulfates • Lead and Lead compounds • Mercuric Oxide Batteries • Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. • Ozone Depleting Substances • Polybrominated Biphenyls (PBBs) • Polybrominated Biphenyl Ethers (PBBEs) • Polybrominated Biphenyl Oxides (PBBOs) • Polychlorinated Biphenyl (PCB) • Polychlorinated Terphenyls (PCT) • Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. • Radioactive Substances • Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
<p>End-of-life Management and Recycling</p>	<p>HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.</p> <p>The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.</p> <p>Global Citizenship Report</p>

Features

	<p>http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html</p> <p>Eco-label certifications</p> <p>http://www8.hp.com/us/en/hp-information/environment/ecolabels.html</p> <p>ISO 14001 certificates:</p> <p>http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/PC_GBU_Product_Design_ISO_14K_Certificate.pdf</p> <p>and</p> <p>http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf</p>
--	---

Technical Specifications

SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	Nominal Operating Voltage	19V
	Average Operating Power	Win 10
	Integrated graphics	
	Discrete Graphics	
	Max Operating Power	< 150W
Temperature	Operating	32° to 95° F (0° to 35° C) (not writing optical) -41° to 95° F (5° to 35° C) (writing optical)
	Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	Operating	10% to 90%, non-condensing
	Non-operating	5% to 95%, 101.6° F (38.7° C) maximum wet bulb temperature
Shock	Operating	Half sine wave shock: 40G, 2ms duration
	Non-operating	Half sine wave shock: 240G, 2ms duration
Random Vibration	Operating	Nominal 0.75 grms
	Non-operating	Nominal 1.50 grms
Altitude (unpressurized)	Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
	Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard Certifications	UL	Yes
	CSA	Yes
	FCC Compliance	Yes
	ENERGY STAR 6.0®	Selected models ³⁶
	EPEAT® 2019	Yes, Silver in U.S. ³⁷
	ICES	Planned
	Australia /	Yes
	NZ A-Tick Compliance	Yes
	CCC	Yes
	Japan VCCI Compliance	Yes
	KC	Yes
	BSMI	Yes
	CE Marking Compliance	Yes
	BNCI or BELUS	Planned
	CIT	Planned
	GOST	Yes
	Saudi Arabian Compliance (ICCP)	Planned
	SABS	Planned
	UKRSERTCOMPUTER	Planned

36. Configurations of the HP EliteBook 1050 G1 that are ENERGY STAR® qualified are identified as HP EliteBook 1050 G1 ENERGY STAR on HP websites and on <http://www.energystar.gov>.

37. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. Visit <http://www.epeat.net> for more information.

Technical Specifications

DISPLAYS

Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.3 + PSR slim N.B.	Outline Dimensions (W x H x D)	350.96 x 216.75 (mm) max.
	Active Area	344.16 x 193.59 (mm) typ.
	Weight	370 g (max)
	Diagonal Size	15.6 (inch)
	Thickness	3.2 (mm) max.
	Interface	eDP 1.3 + PSR (2 lane)
	Surface Treatment	Anti-glare (AG)
	Touch Enabled	N/A
	Contrast Ratio	600:1 (typical)
	Refresh Rate	60 Hz
	Brightness	400 nit typical
	Pixel Resolution	1920 X 1080 (FHD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	72% (sRGB)
Color Depth	6bit (Hi FRC supportive w/ condition to enable)	
Viewing Angle	85/85/85/85 (Left/Right/Down/Up) (typical)	

Technical Specifications

Panel LCD 15.6 inch FHD (1920x1080) Anti-Glare WLED UWVA 72percent cg 650nits eDP 1.4+PSR ultraslim NB Privacy	Outline Dimensions (W x H x D)	350.96 x 216.75 (mm) max.
	Active Area	344.16 x 193.59 (mm) typ.
	Weight	320 g (max)
	Diagonal Size	15.6 (inch)
	Thickness	2.6typ.2.8max (mm)
	Interface	eDP 1.3 + PSR (2 lane)
	Surface Treatment	Anti-glare (AG)
	Touch Enabled	N/A
	Contrast Ratio	Sharing mode: 600:1 (typ.) Privacy mode: 150:1 (typ.) 110:1(min.)
	Refresh Rate	120 Hz
	Brightness	650 nit typical
	Pixel Resolution	1920 X 1080 (FHD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	Sharing mode: 72% (sRGB) Privacy mode: 60% (sRGB)
	Color Depth	6bit + FRC
Viewing Angle	Sharing mode: 85/85/85/85 Privacy mode: 50/50/85/85	

Technical Specifications

Panel LCD 15.6 inch UHD (3840x2160) Anti-Glare WLED UWVA 72percent cg 400nits eDP 1.3 + PSR ultraslim N.B.	Outline Dimensions (W x H x D)	350.96 x 216.75 (mm) max.
	Active Area	344.2176 x 193.6224 (mm) typ.
	Weight	320 g (max)
	Diagonal Size	15.6 (inch)
	Thickness	2.6 (mm) max.
	Interface	eDP 1.3 + PSR (4 lane)
	Surface Treatment	Anti-glare (AG)
	Touch Enabled	N/A
	Contrast Ratio	1200:1 (typical)
	Refresh Rate	60 Hz
	Brightness	400 nit typical
	Pixel Resolution	3840 x 2160 (UHD)
	Format	RGB
	Backlight	LED
	Color Gamut Coverage	72% (sRGB)
	Color Depth	6bit (Hi FRC supportive w/ condition to enable)
	Viewing Angle	85/85/85/85 (Left/Right/Down/Up) (typical)

NOTE: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Technical Specifications

STORAGE

SSD 1TB 2280 PCIe-3x4 NVMe Three Layer Cell single-sided	Form Factor	M.2 2280
	Capacity	1TB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	2900 MB/s~ 3000 MB/s
	Maximum Sequential Write	Up to 2000 MB/s
	Logical Blocks	2,000,409,264
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security, TRIM; L1.2	

SSD 256GB 2280 M2 PCIe-3x4 NVMe TLC	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	2580 MB/s~ 2600 MB/s
	Maximum Sequential Write	1000 MB/s~ 1100 MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security, TRIM; L1.2	

SSD 256GB 2280 M2 SATA-3 Self Encrypted OPAL2 Three Layer Cell	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	ATA-8, SATA 3.0
	Maximum Sequential Read	530 MB/s~ 560 MB/s
	Maximum Sequential Write	500 MB/s~ 530 MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]

Technical Specifications

	Features	ATA Security; TCG Opal 2.0, DIPM; TRIM; DEVSLP
SSD 256GB 2280 PCIe-3x4 NVMe Self Encrypted OPAL2 Three Layer Cell	Form Factor	M.2 2280
	Capacity	256 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	2580 MB/s ~ 2600 MB/s
	Maximum Sequential Write	1000 MB/s ~ 1100 MB/s
	Logical Blocks	500,118,192
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	ATA Security (Option); TCG Opal 2.0; TRIM; L1.2
SSD 2TB 2280 PCIe-3x4 NVMe Three Layer Cell single-sided	Form Factor	M.2 2280
	Capacity	2 TB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	Up to 2900MB/s
	Maximum Sequential Write	Up to 2100 MB/s
	Logical Blocks	3,907,029,168
	Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
	Features	ATA Security, TRIM; L1.2
SSD 512GB 2280 M2 PCIe-3x4 SS NVMe TLC	Form Factor	M.2 2280
	Capacity	512 GB
	NAND Type	TLC
	Height	0.09 in (2.3 mm)
	Width	0.87 in (22 mm)
	Weight	0.02 lb (<10 g)
	Interface	PCIe NVMe Gen3X4
	Maximum Sequential Read	2800 MB/s ~ 2900 MB/s
	Maximum Sequential Write	1000 MB/s ~ 1800 MB/s
	Logical Blocks	1,000,215,215

Technical Specifications

Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security, TRIM; L1.2

SSD 512GB 2280 PCIe-3x4 NVMe Self Encrypted OPAL2 Three Layer Cell

Form Factor	M.2 2280
Capacity	2 TB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (<10 g)
Interface	PCIe NVMe Gen3X4
Maximum Sequential Read	Up to 2900MB/s
Maximum Sequential Write	Up to 2100 MB/s
Logical Blocks	3,907,029,168
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security, TRIM; L1.2

SSD 512GB 2280 M2 SATA-3 Three Layer Cell Federal Information Processing Standard

Form Factor	M.2 2280
Capacity	512 GB
NAND Type	TLC
Height	0.09 in (2.3 mm)
Width	0.87 in (22 mm)
Weight	0.02 lb (<10 g)
Interface	ACS-3, SATA 3.2
Maximum Sequential Read	Up to 530MB/s
Maximum Sequential Write	Up to 400MB/s
Logical Blocks	1,000,215,215
Operating Temperature	32° to 158°F (0° to 70°C) [ambient temp]
Features	ATA Security; TCG Opal 2.0; FIPS; DIPM; TRIM; DEVSLP

NOTE: For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10) is reserved for system recovery software.

Technical Specifications

POWER

AC Adapter 150 Watt Smart PFC Slim Barrel 4.5mm - Vesta	Dimensions	6.02 x 2.60 x .87 in ((153 x 66 x 22 mm)	
	Weight	0.71 lbs (320 g)	
	Input	100 to 240 VAC	
		Input Efficiency	88% min at 115 VAC
		Input frequency range	47 to 63 Hz
		Input AC current	2.9 A at 90 VAC, 1.45 A at 180 VAC
	Output	Output power	150W
		DC output	19.5V
		Hold-up time	5 msec at 115 VAC input
		Output current limit	<16A, Over voltage protection- 29V max automatic shutdown
	Connector	3 pin/grounded, mates with interchangeable cords	
	Environmental Design	Operating temperature	32° to 95° F (0° to 35° C)
		Non-operating (storage) temperature	-4° to 185° F (-20° to 85° C)
		Altitude	32° to 104° F (0° to 40° C)
		Humidity	'-4° to 149° F (-20° to 65° C)
Storage Humidity		0 to 10,000 ft (0 to 3,048 m)	
EMI and Safety Certifications	CE Mark- full compliance with LVD and EMC directives; Worldwide safety standards- IEC950, EN60950, UL1950, Class 1, SELV; Agency approvals- C-UL-US, NORDICS, DENAN, EN55022 Class B, FCC Class B, CISPR22 Class B, CCIB, NOM-1 NYCE; MTBF- over 200,000 hours at 25°C ambient condition.		

Battery ZG 4 Cell WHr 64 Long Life -PL Fast Charge	Dimensions (H x W x L)	7.9 x 3.49 x 0.32 in (20.08 x 8.86 x 0.81cm)	
	Weight	0.619lb (281g)	
	Cells/Type	4-cell; Polymer	
	Energy	Voltage	15.4V
		Amp-hour capacity	4.155Ah
		Watt-hour capacity	64Wh
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)
		Operating (Discharging)	14° to 140° F (-10° to 60° C)
	Fuel Gauge LED	No	
	Optional Travel Battery Available	No	

Technical Specifications

Battery ZG 6 Cell WHr 95 Long Life -PL Fast Charge	Dimensions (H x W x L)	13.02 x 3.51 x 0.319 in (33.08 x 8.92 x 0.81 cm)
	Weight	1.12lb (420g)
	Cells/Type	6-cell; Polymer
	Energy	Voltage 11.55V
		Amp-hour capacity 8.31Ah
		Watt-hour capacity 95Wh
	Temperature	Operating (Charging) 32° to 122°F (0° to 50° C)
		Operating (Discharging) 14° to 140° F (-10° to 60° C)
	Fuel Gauge LED	No
	Warranty	3 year
	Optional Travel Battery Available	No

* 3-year platform warranty is required for a 3-year Long Life Battery warranty.

Docking station model	Total number of supported displays (incl. the notebook display)	Max.resolutions supported	Dock Connectors	Technical limitations
HP Elite 120W TB3 Dock	3	Dual 4K @ 60Hz	2xDP, 1xVGA, 1xTB	Dual 4k only with one display in to DP and + TB port or USB-C alt mode + TB port
HP USB-C Universal Dock	3	Single 4K @ 60Hz (3840 x 1440)	1xHDMI, 2xDP	
HP Thunderbolt Dock 230W G2	1	4096 x 2160 @ 60Hz	1 USB-C™ data and charging port (15W) 1 USB-C™ DisplayPort™ – data and charging (15W) 1 USB-C™ Thunderbolt™ port 2 USB 3.0 ports 1 USB 3.0 charging port 1 Power Adapter port 2 DisplayPort™ ports 1 Ethernet port (10/100/1000) 1 combo audio port 1 Security lock slot	
	2	4096 x 2160 @ 60Hz		
	3	Dual 4K @ 60Hz		
	4 displays	supported but is dependent on host capability		
HP Thunderbolt Dock Audio				
HP USB-C Travel Dock	2	Dual 4K @ 60Hz	2xDP	Single external display Only HDMI or VGA at the time
HP USB-C Mini Dock	2	Single 5K @ 60Hz	1xHDMI, 1xVGA	Single external display Only HDMI or VGA at the time

Technical Specifications

COUNTRY OF ORIGIN

China

Summary of Changes

Date of change:	Version History:		Description of change:
June 28, 2018	v1 to v2	Added	Environmental tab
August 15, 2018	v2 to v3	Updated	Display section, Software Workwise, at a glance and Docking
September 26, 2018	v3 to v4	Updated	Power section, footnote 33
October 5, 2018	v4 to v5	Update	Compatibility section and it's specs added
October 16, 2018	v5 to v6	Update	Specs for HP Thunderbolt Dock 230W G2 compatibility added.
October 17, 2018	v6 to v7	Update	Footnotes 32 and 33 set on Power section page 13.
February 13, 2019	v7 to v8	Removed	Phonewise Software
May 30, 2019	v8 to v9	Updated	Lock Slot
June 3, 2019	v9 to v10	Updated	Security Lock
June 7, 2019	v10 to v11	Updated	EPEAT
October 10, 2019	V11 to v12	Updated	At a glance Section, Thunderbolt™

Copyright © 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. NVIDIA, the NVIDIA logo, GeForce are trademarks and/or registered trademarks of NVIDIA Corporation in the U.S. and other countries. USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum. SD, SDHC and SDXC are registered trademarks of SD-3C in the United States, other countries or both. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.