
Overview

HP V214b 20.7-inch Monitor



- 1.
- 4. Auto-Adjustment
- 2. Minus ("-")/ Information



Technical Specifications

Model: 3FU54AA

Panel	Туре	20.7-inch TN with LED backlight
	Viewable Image Area (diagonal)	52,58 cm (20.7 in) widescreen; diagonally measured
	Panel Active Area (W × H)	45,79 x 25,76 cm (18.03 × 10.14 in)
	Resolution	1920 x 1080 @ 60 Hz (Full HD)
	Aspect Ratio	16:9
	Viewing Angle*	Up to 90° horizontal/65° vertical typical
	Brightness*	200 cd/m ²
	Contrast Ratio*	450:1 Static (Minimum); 600:1 Static (Typical); 5,000,000:1 Dynamic (DCR)
	Response Times*	5 ms On/Off
	Pixel Pitch*	0.2385 mm
	Pixels Per Inch (PPI)*	108
	Backlight Lamp Life* (to half brightness)	30,000 hours minimum
	Panel Bit Depth	6-bit (Hi-FRC)
	Color Production*	Can display up to 16.7 million colors with the use of FRC technology
	Color Gamut* (Typical)	72% (NTSC)
	Default Color Temperature	Neutral (6500)
	Low Blue Light Modes	Yes

* Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

User Controls	Buttons or Switches	Menu/OK, Minus ("-")/Information, Plus ("+") /Viewing mode Auto-Adjustment, Power		
	User-Assignable Function Buttons	Yes, 3		
	On Screen Display (OSD) User Controls	Brightness, Contrast, Color Control, Image Control, Power Control, Menu Control, Management, Language, Information, Exit		
	Audio Controls	N/A		
	Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)		
Signal Interface/	Horizontal Frequency	30–80 kHz		
Performance	Vertical Frequency	50-60 Hz		
	Native Resolution	1920 x 1080 @ 60 Hz		
	Preset Graphic Modes (non-interlaced)	640 x 480 @ 60Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz		



Technical Specifications

Video/Other Inputs Audio Power	Maximum Pixel Clock Speed Anti-Glare Plug and Play Input Connectors Cables Included Speakers Power Supply	1280 x 800 @ 6 1280 x 1024 @ 1440 x 900 @ 6 1600 x 900 @ 6 1680 x 1050 @ 1920 x 1080 @ 170 MHz Yes Yes (1) VGA (1) VGA 1,5 m (4 N/A Internal	60 Hz 0 Hz 0 Hz 60 Hz 60 Hz	
	Input Power	100 - 240 VAC 50/60 Hz		
	Maximum Power	20 W		
	Typical Power	16 W	16 W	
	Sleep Power	0.5 W		
	Power Cable Length	1,5 m (4.92 ft)		
Mechanical	Dimensions (W × D × H)	Unpacked w/stand (lowest setting) Unpacked w/o stand (head only)	48,94 x 36,27 x 19,76 cm (19.26 x 14.28 x 7.78 in) 48,94 x 30,06 x 4,8 cm (19.26 x 11.84 x 1.89 in)	
		Packaged	55,5 x 12,7 x 39,5 cm (21.85 x 4.99 x 15.35 in)	
	Weight	•	(21.85 x 4.99 x 15.35 in)	
	Weight	Packaged		
	Weight	Packaged Head Only	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb)	
Ergonomic	Weight Detachable Stand	Packaged Head Only Unpacked	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb)	
Ergonomic Features	-	Packaged Head Only Unpacked Packaged	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed	
-	Detachable Stand	Packaged Head Only Unpacked Packaged Yes, ships detac	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical	
Features	Detachable Stand Tilt Range	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F)	
Features	Detachable Stand Tilt Range Temperature - Operating	Packaged Head Only Unpacked Packaged Yes, ships detact -5° to + 11° vert 5° to 35° C (41°	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F)	
Features	Detachable Stand Tilt Range Temperature - Operating Temperature - Non-operating	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert 5° to 35° C (41° -20° to 60° C (-	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F)	
Features	Detachable Stand Tilt Range Temperature - Operating Temperature - Non-operating Humidity - Operating	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert 5° to 35° C (41° -20° to 60° C (- 20% to 80% not	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F) n-condensing	
Features	Detachable Stand Tilt Range Temperature - Operating Temperature - Non-operating Humidity - Operating Humidity - Non-operating	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert 5° to 35° C (41° -20° to 60° C (20% to 80% not 5% to 95%	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F) n-condensing to 16,400 ft)	
Features	Detachable Stand Tilt Range Temperature - Operating Temperature - Non-operating Humidity - Operating Humidity - Non-operating Altitude - Operating	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert 5° to 35° C (41° -20° to 60° C (- 20% to 80% not 5% to 95% O to 5,000 m (0	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F) n-condensing to 16,400 ft)	
Features	Detachable Stand Tilt Range Temperature - Operating Temperature - Non-operating Humidity - Operating Humidity - Non-operating Altitude - Operating Altitude - Non-operating	Packaged Head Only Unpacked Packaged Yes, ships detac -5° to + 11° vert 5° to 35° C (41° -20° to 60° C (- 20% to 80% not 5% to 95% O to 5,000 m (0 0 to 12,192 m (0	(21.85 x 4.99 x 15.35 in) 2,6 kg (5.73 lb) 3 kg (6.61 lb) 4,4 kg (9.7 lb) thed tical to 95° F) 4° to 140° F) n-condensing to 16,400 ft)	



Technical Specifications

	Low Halogen ¹		N/A	
	Mercury-Free Display Ba	acklights	Yes	
otions ach sold parately)	HP LCD Monitor Quick Re number EM870AA ⁴	elease — Part	An easy-to-use, VESA-compliant, LCD monitor mounting solution that allows you to quickly and securely attach an LCD monitor to a variety of stands, brackets, arms or wall mounts. For more information, refer to this product's QuickSpecs document.	
	HP Business PC Security number N3R93AA	Lock V2 Kit — Part	Help prevent chassis tampering and secure your PC and display in workspaces and public areas. Simply route the cable through the PC's lock slot and your display, anchor to a desk, table, or other fixed surface, and lock with your individual key. A master key configuration is also available upon request.	
hat's in the box?	Monitor and Accessories		HP V214b 20.7-inch Monitor, AC power cable 1,5 m (4.92 ft), VGA cable 1,5 m (4.92 ft)	
	Documentation		CD (includes user guide, warranty, drivers)	
	Software		N/A	
Other	User Guide Languages	English, Simplified Chinese, Traditional Chinese		
	Warranty Languages	Simplified Chinese		
	Color	Black		
	VESA Mounting	100 mm VESA mount		
	Security Lock-Ready	Yes		
	Country of Origin	Origin China		
Certification	China application			
and Compliance	CB/CCC/CEL/CECP/SEPA/BSMI/WEEE/TUV-Low Blue Light, Microsoft WHQL Certification (Win 7, Win 8, Win 10/RS1/RS2/RS3)			
Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.			
Service and Warranty	Protected by HP, including a 3-year standard limited warranty (may vary by region). Optional HP Care Pack Services are extended service contracts that extend your protection beyond the standard warranties. ²			

Technical Specifications

Copyright © 2018 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries.

- 1. External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.
- 2. Service levels and response times for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit: www.hp.com/go/cpc.



Change Log

Change Log		

